

Speed dome day/night camera



DS2AF1-516

Speed dome dual camera; module 1/4" Sony Double Scan CCD; 540TVL/570 TVL; moto-zoom 3,5-105mm/F1.4-3,7; 30x optical zoom, 12x digital zoom; min. illumination 0.2Lux/F1.4 (color), 0.02Lux/F1.4 (b/w with SlowShutter); S/N ratio >50dB; 256 presets, 8 tours, 8 patterns; OSD; autofocus; WDR (auto/manual); compass; pan speed 0.1-300

Technical parameters

Product type	PTZ outdoor camera
Camera module	day/night
Sensor	CCD 1/4" Sony Double Scan
Resolution	540 TVL / 570 TVL
Sensitivity	0,2Lux/F1.4 (color), 0.02Lux/F1.4 (b/w with SlowShutter)
Built-in moto-zoom	3,5-105mm/F1.4-3,7
Zoom	30x optical, 12x digital
P/T speed	manual: pan speed 0,1-300
Presets	256 presets, 8 tours (up to 32 presets), 4 patterns (up to 10min)
Special functions	autofocus, OSD menu, compass, 3kV surge protection
alarm inputs / outputs	7 inputs / 2 output
Application	Outdoor; IP66
mount	depends of bracket (wall, corner or pole mount), recommended wall bracket DS1614ZJ
Voltage	24VAC/45W (with heater)
Opertion temp.	-30
Dimensions	o220mm x 299mm(h) without bracket
Weight	5kg